### **SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

PRODUCT NAME: EPOXY.COM #2006

PRODUCT CODES: 2006

SUPPLIER: Epoxy Systems, Inc.

STREET ADDRESS: 20774 West Pennsylvania Ave.

CITY, STATE, ZIP: Dunnellon, FL 34431

INFORMATION PHONE: 352-489-1666 EMERGENCY PHONE: PERS 800-633-8253

FAX PHONE: 352-489-1625

PREPARED BY: Katey Fontaine

DATE REVISED: 11/13/2013

#### **SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS**

INGREDIENT		CAS NO.	OSHA PEL	ACGIH TLV	OSHA STEL	WEIGHT %			
REACTION PRODUCTS OF EPICHLOROHYDRIN									
<b>BISPHENOL A</b>		25068-38-6	NONE	NONE	NONE				
EXTENDER	NON HAZARDOUS IN LIQUI	D FORM	10mg/m3	10mg/m3	5mg/m3				
PIGMENT	NON HAZARDOUS IN LIQUII	D FORM	10mg/m3	10mg/m3	5mg/m3				
ALKYLATED PHE	NOL	31091-95-9	NONE	NONE	NONE				
EXTENDER	NON HAZARDOUS IN LIQUI	D FORM	NONE	5MG/M3	NONE				
<b>FUMED SILICA</b>		112945525	NONE	80mg/m3	NONE				

SECTION 2 NOTES: \*No toxic chemical(s) subject to reporting requirements of section 313 of Title III and of 40 CFR 372 are present.

### **SECTION 3: PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE AND ODOR: WHITE./TAN GEL

BOILING POINT OR RANGE: 200 +F VAPOR DENSITY (AIR = 1): N/A SPECIFIC GRAVITY (H2O = 1): 1.4 EVAPORATION RATE: N/A

SOLUBILITY IN WATER: NEGLIGIBLE

**SECTION 3 NOTES:** 

# **SECTION 4: FIRE-FIGHTING MEASURES**

FLAMMABLE LIMITS IN AIR, UPPER: not available (% by volume) LOWER: not available

FLASH POINT: 200+F METHOD USED: SETA FLASH

**EXTINGUISHING MEDIA:** 

FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIRE FIGHTING PROCEDURES:

DO NOT ENTER CONFINED AREA WITHOUT FULL BUNKER GEAR INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS. COOL ALL FIRE EXPOSED CONTAINERS WITH WATER.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** 

NONE KNOWN.

**SECTION 4 NOTES:** 

# **SECTION 5: STABILITY AND REACTIVITY**

STABILITY:

**STABLE** 

CONDITIONS TO AVOID (STABILITY):

AVOID EXCESSIVE HEAT OR OPEN FLAMES.

**INCOMPATIBILITY (MATERIAL TO AVOID):** 

CAN REACT VIGOROUSLY WITH STRONG OXIDIZING AGENTS AND STRONG LEWIS ACIDS OR MINERAL ACIDS.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

CO2, ALDEHYDES, ACIDS. REACTION WITH SOME CURING AGENTS CAN GENERATE LARGE AMOUNTS OF HEAT.

HAZARDOUS POLYMERIZATION:

WILL NOT OCCUR.

**SECTION 5 NOTES:** 

#### **SECTION 6: HAZARDS IDENTIFICATION**

HMIS HAZARD CLASSIFICATION

HEALTH: 2 FLAMMABILITY: 1 REACTIVITY: 0 PERSONAL PROTECTIVE EQUIPMENT: B

POTENTIAL HEALTH EFFECTS

EYES:

MAY CAUSE IRRITATION BUT NO CORNEAL INJURY IS LIKELY.

SKIN:

MAY CAUSE IRRITATION OR ALLERGIC SKIN RESPONSE.

INGESTION:

THIS MATERIAL HAS A PROBABLE LOW ACUTE ORAL TOXICITY.

INHALATION:

NO GUIDE FOR CONTROL KNOWN, HOWEVER, EXPOSURE TO HEATED VAPORS CAN CAUSE IRRITATION TO THE NOSE, THROAT OR MUCOUS MEMBRANES..

**HEALTH HAZARDS (ACUTE AND CHRONIC):** 

EPOXY RESINS CAN CAUSE SENSITIZATION BY EXPOSURE THROUGH CONTACT OR HIGH CONCENTRATION OF VAPOR. EYES:

INJURY IF UNLIKELY BUT STAIN FOR EVIDENCE OF CORNEAL INJURY.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: RESPIRATORY CONDITIONS OR OTHER ALLERGIC AILMENTS.

**CARCINOGENICITY** 

OSHA: NO NTP: NO IARC: NO

ADDITIONAL CARCINOGENICITY INFORMATION:

NO LISTED INGREDIENTS OF THIS PRODUCT ARE REGULATED AS CARCINOGENS.

## **SECTION 7: FIRST AID MEASURES**

#### EYES:

FLUSH EYES WITH WATER FOR AT LEAST FIFTEEN MINUTES AND CONSULT A PHYSICIAN.

SKIN

SKIN CONTACT WILL NORMALLY CAUSE NO MORE THAN IRRITATION BUT WASH AFFECTED AREA WITH SOAP AND WATER AND REMOVE CONTAMINATED CLOTHING PROMPTLY.

INGESTION:

LOW IN TOXICITY, INDUCE VOMITING ONLY IF LARGE AMOUNTS OF MATERIAL ARE INGESTED, AND OTHERWISE DO NOT INDUCE VOMITING. IN EITHER CASE CONSULT WITH A PHYSICIAN.

INHALATION:

REMOVE VICTIM TO FRESH AIR AND ADMINISTER OXYGEN IF NECESSARY.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:

**SECTION 7 NOTES:** 

### **SECTION 8: RELEASE MEASURES**

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

WEAR RESPIRATOR AND PROTECTIVE CLOTHING. SHUT OFF THE SOURCE AT THE LEAK. REMOVE EXCESS WITH VACUUM TRUCK AND TAKE UP THE REMAINDER WITH AN ABSORBENT SUCH AS CLAY AND PLACE IN DISPOSAL CONTAINERS. FLUSH AREA WITH WATER TO REMOVE RESIDUE.

**SECTION 8 NOTES:** 

### **SECTION 9: WASTE DISPOSAL**

**WASTE DISPOSAL METHOD:** 

DISPOSE OF THE MATERIAL IN A WASTE DISPOSAL SITE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL LAW.

### SECTION 10: HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

STORE IN A COOL DRY PLACE. SEAL ALL PARTIALLY USED CONTAINERS. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. MIXED MATERIALS CONTAIN THE HAZARDS OF ALL THE COMPONENTS, THEREFORE, READ THE MSDS'S OF ALL THE COMPONENTS PRIOR TO USING MATERIAL. PROPERLY LABEL ALL CONTAINERS OTHER PRECAUTIONS:

AVOID ALL SKIN CONTACT. AVOID BREATHING VAPORS GENERATED FROM THE MATERIAL. OBSERVE CONDITIONS OF GOOD GENERAL HYGIENE AND SAFE WORKING PRACTICES. CONTAMINATED LEATHER ARTICLES CAN NOT BE CLEANED AND MUST BE DISCARDED IF CONTAMINATED WITH THIS PRODUCT. WASH ALL CONTAMINATED CLOTHING PRIOR TO THE REUSE THEREOF

**SECTION 10 NOTES:** 

#### SECTION 11: EXPOSURE CONTROLS/PERSONAL PROTECTION

## RESPIRATORY PROTECTION:

USE A NIOSH APPROVED RESPIRATOR AS REQUIRED TO PREVENT OVER EXPOSURE TO VAPOR IN ACCORDANCE WITH 29 CFR 1910.134. GENERAL EXHAUST IS USUALLY SUFFICIENT IN LIEU OF NIOSH RESPIRATOR

**VENTILATION:** 

GENERAL EXHAUST IS USUALLY SUFFICIENT TO CONTROL VAPORS AND EXPOSURE HAZARDS

**PROTECTIVE GLOVES:** 

**IMPERVIOUS GLOVES - NEOPRENE OR RUBBER** 

**EYE PROTECTION:** 

SPLASH GOGGLES OR GLASSES WITH SIDE SHIELDS.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

WEAR BODY COVERING CLOTHING AND OTHER COVERINGS AS NECESSARY SUCH AS APRON AND APPROPRIATE FOOTWEAR TO AVOID CONTACT WITH MATERIAL.

**WORK HYGIENIC PRACTICES:** 

**OBSERVE GOOD GENERAL HYGIENIC PRACTICES.** 

**SECTION 11 NOTES:** 

### **SECTION 12: DISCLAIMER**

DISCLAIMER: The information Contained herein is based on the data available and is believed to be accurate, However, the supplier makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

### **SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

PRODUCT NAME: NP103M PART B PRODUCT CODES: 103M B

SUPPLIER: Epoxy Systems, Inc.

STREET ADDRESS: 20774 West Pennsylvania Ave. CITY, STATE, ZIP: Dunnellon, FL 34431

INFORMATION PHONE: 352-489-1666 EMERGENCY PHONE: PERS 800-633-8253

FAX PHONE: 352-489-1625

PREPARED BY: Katey Fontaine

**DATE REVISED: 11/13/2013** 

### **SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS**

INGREDIENT TETRAETHYLENE TOFA, REACTION DIETHYLENETRIA	PRODUCTS WITH TEPA	<u>CAS NO.</u> 112-57-2 68953-36-6 111-40-0	OSHA PEL NONE NONE 1PPM	ACGIH TLV NONE NONE 1PPM	OSHA STEL NONE NONE NONE	WEIGHT %		
MODIFIED-ALIPHATIC POLYAMINE								
	NJTSR# IS 05995500-	5449P	NONE	NONE	NONE			
*BISPHENOL A		80-05-7	NONE	NONE	NONE	1		
<b>FUMED SILICA</b>		112945525	NONE	80mg/m3	NONE			
PIGMENT	NON HAZARDOUS IN LIQU	ID FORM	3.5PPM	3.4PPM	NONE			
ALKYLATED PHENOL 31091-95		31091-95-9	NONE	NONE	NONE			
EXTENDER	NON HAZARDOUS IN LIQUI	D FORM	10mg/m3	10mg/m3	5mg/m3			

#### **SECTION 2 NOTES:**

### **SECTION 3: PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE AND ODOR: GRAY/BLACK GEL

BOILING POINT OR RANGE: 631F VAPOR DENSITY (AIR = 1): N/A SPECIFIC GRAVITY (H2O = 1): 1.0 EVAPORATION RATE: N/A SOLUBILITY IN WATER: NEGLIGIBLE

**SECTION 3 NOTES:** 

### **SECTION 4: FIRE-FIGHTING MEASURES**

FLAMMABLE LIMITS IN AIR, UPPER: not available (% by volume) LOWER: not available

FLASH POINT: 200+F METHOD USED: SETA FLASH

**EXTINGUISHING MEDIA:** 

FOAM, ALCOHOL FOAM, CO2, WATER FOG SPECIAL FIRE FIGHTING PROCEDURES:

TOXIC FUMES WILL BE EVOLVED WHEN THIS MATERIAL IS INVOLVED IN A FIRE. A SELF-CONTAINED BREATHING APPARATUS SHOULD BE AVAILABLE FOR FIRE FIGHTING. COOL FIRE EXPOSED CONTAINERS WITH WATER.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** 

NONE KNOWN.

**SECTION 4 NOTES:** 

## **SECTION 5: STABILITY AND REACTIVITY**

STABILITY:

STABLE

CONDITIONS TO AVOID (STABILITY):

AVOID CONTACT WITH OPEN FLAMES AND ALL SOURCES OF IGNITIONS AND SPARKS.

INCOMPATIBILITY (MATERIAL TO AVOID):

<sup>\*\*\*</sup>Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present.\*\*\*

AVOID CONTACT WITH STRONG OXIDIZING AGENTS MINERAL ACIDS AND EPOXY RESINS IN UNCONTROLLED AMOUNTS. HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

CO, CO2, NOX

HAZARDOUS POLYMERIZATION:

WILL NOT OCCUR.

**SECTION 5 NOTES:** 

### **SECTION 6: HAZARDS IDENTIFICATION**

HMIS HAZARD CLASSIFICATION

HEALTH: 2 FLAMMABILITY: 1 REACTIVITY: 0 PERSONAL PROTECTIVE EQUIPMENT: G

POTENTIAL HEALTH EFFECTS

EYES:

WILL CAUSE BURNS TO EYES. HIGH VAPOR CONCENTRATIONS CAN CAUSE SEVERE IRRITATION TO THE EYES.

SKIN:

WILL CAUSE BURNS TO THE SKIN

INGESTION:

LIQUID CAN CAUSE SEVERE DAMAGE TO MUCOUS MEMBRANES IF SWALLOWED.

INHALATION:

HIGH CONCENTRATIONS OF VAPOR CAN CAUSE IRRITATION TO THE RESPIRATORY TRACT, NAUSEA, AND DIZZINESS.

**HEALTH HAZARDS (ACUTE AND CHRONIC):** 

PROLONGED OR REPEATED EXPOSURE MAY CAUSE ASTHMA AND SKIN SENSITIZATION OR OTHER ALLERGIC RESPONSES.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

RESPIRATORY CONDITIONS OR OTHER ALLERGIC AILMENTS.

**CARCINOGENICITY** 

OSHA: NO NTP: NO IARC: NO

ADDITIONAL CARCINOGENICITY INFORMATION:

NO LISTED INGREDIENTS OF THIS PRODUCT ARE REGULATED AS CARCINOGENS.

### **SECTION 7: FIRST AID MEASURES**

EYES

FLUSH EYES WITH WATER FOR AT LEAST FIFTEEN MINUTES WHILE LIFTING UPPER AND LOWER LIDS. GET IMMEDIATE MEDICAL ASSISTANCE.

SKIN:

FLUSH SKIN WITH WATER FOR AT LEAST 15 MINUTES AND REMOVE ALL CONTAMINATED CLOTHING IMMEDIATELY. GET MEDICAL ATTENTION IF REDDENING OR SWELLING OCCURS.

INGESTION:

DO NOT INDUCE VOMITING. DILUTE BY GIVING WATER OR MILK TO DRINK IF VICTIM IS CONSCIOUS. GET MEDICAL ATTENTION IMMEDIATELY.

INHALATION:

REMOVE VICTIM TO FRESH AIR AND ADMINISTER OXYGEN IF NECESSARY.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:

**SECTION 7 NOTES:** 

## **SECTION 8: RELEASE MEASURES**

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

AVOID CONTACT WITH MATERIAL. WEAR THE APPROPRIATE SAFETY EQUIPMENT. STOP SPILL AT SOURCE, DYKE AREA TO PREVENT SPREADING. PUMP LIQUID TO SALVAGE TANK. TAKE UP REMAINDER WITH CLAY OR OTHER ABSORBENT AND PLACE IN DISPOSAL CONTAINERS.

**SECTION 8 NOTES:** 

## **SECTION 9: WASTE DISPOSAL**

**WASTE DISPOSAL METHOD:** 

DISPOSE OF MATERIAL AS A HAZARDOUS WASTE ACCORDING TO FEDERAL, STATE, AND LOCAL REGULATIONS.

# SECTION 10: HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

AVOID ALL SKIN CONTACT. AVOID BREATHING VAPORS. RESEAL PARTIALLY USED CONTAINERS. PROPERLY LABEL ALL CONTAINERS. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING, OR USING TOILET FACILITIES. OBSERVE CONDITIONS OF GOOD INDUSTRIAL HYGIENE AND SAFE WORKING PRACTICES. OTHER PRECAUTIONS:

MIXED MATERIALS CONTAIN THE HAZARDS OF ALL THE COMPONENTS, THEREFORE, READ THE MSDS OF ALL COMPONENTS TO BECOME FAMILIAR WITH ALL HAZARDS PRIOR TO USING THIS PRODUCT.

### SECTION 11: EXPOSURE CONTROLS/PERSONAL PROTECTION

**RESPIRATORY PROTECTION:** 

NIOSH APPROVED RESPIRATOR PROTECTION REQUIRED IN THE ABSENCE OF PROPER ENVIRONMENTAL CONTROLS. FOR EMERGENCIES A SELF-CONTAINED BREATHING APPARATUS OR A FULL FACE RESPIRATOR IS RECOMMENDED. VENTILATION:

AVOID BREATHING VAPORS. VENTILATION MUST BE SUFFICIENT TO CONTROL VAPORS.

**PROTECTIVE GLOVES:** 

**IMPERVIOUS GLOVES - NEOPRENE OR RUBBER** 

**EYE PROTECTION:** 

SPLASH GOGGLES OR GLASSES WITH SIDE SHIELDS.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

WEAR BODY COVERING CLOTHING AND OTHER COVERINGS AS NECESSARY SUCH AS APRON AND APPROPRIATE FOOTWEAR TO AVOID CONTACT WITH MATERIAL.

**WORK HYGIENIC PRACTICES:** 

**OBSERVE GOOD GENERAL HYGIENIC PRACTICES.** 

**SECTION 11 NOTES:** 

# **SECTION 12: DISCLAIMER**

DISCLAIMER: The information Contained herein is based on the data available and is believed to be accurate, However, the supplier makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.