MATERIAL SAFETY DATA SHEET

PRODUCT NAME: EPOXY.COM #32FLEX EPOXY PART A HMIS CODES: H F R P PRODUCT CODE: #32 A 1 1 0 B

SECTION 1: MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: EPOXY SYSTEMS, INC.

ADDRESS: 20774 West Pennsylvania Ave

Dunnellon, FL 34431

EMERGENCY NUMBER: 1-800-633-8253 **DATE PRINTED:** 08/05/08 **INFORMATION NUMBER:** 352-489-1666 PREPARER: K. Fontaine

SECTION 2: HAZARDOUS INGREDIENTS

ACGIH

HAZARDOUS COMPONENTS CAS NUMBER OSHA PEL TLV WT % CARCINOGEN Epoxy Resin 25068-38-6 NE NE 60-80 Polypropylene Glycol 9072-62-2 NE NE 20-40

Glycidyl Ether

Substances listed are present in concentration of 1% or greater, or 0.1% if cited as a potential Carcinogen in the OSHA hazards communication standard. Where proprietary ingredient is listed, the identity is available as provided in 29 CFR 1910.1200.

NE - Not Established

SECTION 3: PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT NA

VAPOR DENSITY Heavier than Air

VAPOR PRESSURE N/A VOC

Negligible SOLUBILITY IN WATER

APPEARANCE AND ODOR Clear Liquid, mild odor

SPECIFIC GRAVITY (H20=1) 1.14

EVAPORATION RATE Slower than N-Butyl Acetate

SECTION 4: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: >200° F METHOD USED: SFCC

FLAMMABLE LIMITS IN AIR BY VOLUME LOWER: Not determined UPPER: Not determined

EXTINGUISHING MEDIA: Water spray, dry chemical, Foam, Carbon Dioxide OSHA FLAMMABILITY CLASSIFICATION: Combustible liquid, Class III A SPECIAL FIRE FIGHTING PROCEDURES: Firefighters and others exposed to vapors of combustion should wear self-contained breathing apparatus and full protective clothing to prevent contact with skin and eyes. UNUSUAL FIRE AND EXPLOSION HAZARDS: May produce hazardous fumes or

hazardous decomposition products.

SECTION 5: REACTIVITY DATA

STABILITY: Stable

CONDITIONS TO AVOID: N/A

INCOMPATIBILITY (MATERIALS TO AVOID): Strong Amines and Acids HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Carbon Monoxide, Carbon

Dioxide, Aldehydes and Acids.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 6: HEALTH HAZARD DATA

HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

INHALATION: Heating can generate vapors that could cause headache, nauseam dizziness, and respiratory irritation if inhaled.

SKIN CONTACT: Prolonged or repeated contact of product with skin may cause irritation and could result in dermititis. May cause sensitization or other allergic reaction.

EYE CONTACT: Direct contact of product with eyes can cause irritation.

INGESTION: Slightly toxic.

HEALTH HAZARDS (ACUTE AND CHRONIC):

CARCINOGENICITY: NTP CARCINOGEN: NO IARC MONOGRAPHS: NO

OSHA REGULATED: No

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Flush eyes with generous amounts of water for at least 15 minutes. Get immediate medical attention.

SKIN: Wash affected areas with water while removing contaminated clothing. Launder contaminated clothing before reuse.

INGESTION: If swallowed, DO NOT INDUCE VOMITING. Dilute with water
 and call a physician immediately. Never give fluids or induce
 vomiting if victim is unconscious or having convulsions.

INHALATION: Move to fresh air. Aid in breathing, if necessary,
 and get immediate medical attention.

SECTION 7: PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Soak up in absorbent material or scrape up. Residual can be removed with non-flammable solvent.

WASTE DISPOSAL METHOD: Burn in adequate incinerator or bury in an approved landfill in accordance with local, state of Federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store in a cool, dry, well ventilated area away from excessive heat or open flame.

OTHER PRECAUTIONS: Avoid breathing of vapors. Practice good personal hygiene and exercise caution to avoid skin and eye contact.

SECTION 8: CONTROL MEASURES

RESPIRATORY PROTECTION: NIOSH/MSHA approved organic vapor respirator when vapors are generated above the permissible limit.

VENTILATION: Good general mechanical ventilation and local exhaust.

PROTECTIVE GLOVES: Plastic or rubber.

EYE PROTECTION: Safety glasses with side shields or chemical goggles. **OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** Clean body covering clothing. A safety shower and eye wash facility should be available.

WORK/HYGIENIC PRACTICES: Wash thoroughly before eating, drinking, or smoking.

SECTION 9: REGULATORY INFORMATION

SARA TITLE III SECTION 313: Unless shown below, this product does not contain the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372:

CAS # Chemical Name Percent by Weight 106-89-8 Epichlorohydrin trace

PROP 65 (CARCINGEN): Unless shown below, this product does not contain chemicals known to the state of California to cause cancer.

CAS # Chemical Name Percent by Weight

PROP 65 (TERATOGENIC): Unless shown below, this product does not contain chemicals known to the state of California to cause birth defects or other reproductive harm.

CAS # Chemical Name Percent by Weight
None

PROP 65 (CARCINOGENIC & TERATOGENIC): Unless shown below, this product does not contain chemicals known to the state of California to cause cancer or birth defects or other reproductive harm.

CAS # Chemical Name Percent by Weight

HAZARDOUS WASTE INFORMATION: Unless shown below, this product is not a hazardous waste according to definitions found in CFR-40.

STATE OF MICHIGAN CRITICAL MATERIALS: Unless shown below, this product does not contain ingredients appearing on the State of Michigan Critical Materials List.

CAS # Chemical Name Percent by Weight
None

D. O. T. PROPER SHIPPING NAME: Synthetic Resin Liquid

PROPER SHIPPING NAME: Synthetic Resin Liquid

HAZARD CLASS: non-hazardous

UN/NA ID NUMBER:

SECTION 10: DISCLAIMER

Data and recommendations presented herein are based upon our and other researchers and are believed to be accurate. The products discussed are distributed without warranty (expressed or implied) and the customer shall make his own determination of suitability for his particular purpose.