# MATERIAL SAFETY DATA SHEET EPOXY.COM # 464 100% SOLIDS URETHANE COATING PART A

PRODUCT NAME: EPOXY.COM # 464100% SOLIDS URETHANE COATING PART A HMIS CODES: H F R P

**PRODUCT CODE:** 464 A 2 3 0 -

# **SECTION 1: MANUFACTURER IDENTIFICATION**

MANUFACTURER'S NAME: EPOXY SYSTEMS, INC. ADDRESS: 20774 West Pennsylvania Ave

Dunnellon, FI 34431

 EMERGENCY NUMBER:
 1-800-633-8253 PERS
 DATE PRINTED:
 09/17/08

 INFORMATION NUMBER:
 1-352-489-1666
 NAME OF PREPARER:
 K. Fontaine

#### SECTION 2: HAZARDOUS INGREDIENTS/SARA III INFORMATION

HAZARDOUS COMPONENTSCAS NUMBEROSHA PELACGIH TLVWT %Urethane PrepolymerMixtureNENE80-90Isophorone diisocyanate4098-71-90.0050.005 ppm1-3

Substances listed are present in concentration of 1% or greater, or 0.1% if cited as a potential Carcinogen in the OSHA hazards communication standard. Where proprietary ingredient is listed, the identity is available as provided in 29 CFR 1910.1200.

NE - Not Established

#### SECTION 3: PHYSICAL/CHEMICAL CHARACTERISTICS

SOLUBILITY IN WATER : No

APPEARANCE AND ODOR : Clear Liquid with musty odor

WEIGHT PER GALLON : 9.2 lbs. (± 0.25)
EVAPORATION RATE : Slower than ether
PERCENT VOC BY VOLUME : Less than 1%

# **SECTION 4: FIRE AND EXPLOSION HAZARD DATA**

FLASH POINT: >200° F METHOD USED: TCC

FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: Not determined UPPER: Not determined EXTINGUISHING MEDIA: Foam, Water spray (fog), CO2, Dry Chemical

SPECIAL FIRE FIGHTING PROCEDURES: Wear NIOSH/MSHA approved self contained breathing apparatus and full

protective clothing. Use water to keep fire exposed containers cool.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Pressure may build up in containers and create an explosion hazard.

# **SECTION 5: REACTIVITY DATA**

STABILITY: Stable

INCOMPATIBILITY (MATERIALS TO AVOID): Oxidizing agents, strong acids & bases

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Carbon monoxide, carbon dioxide, nitrogen oxides and organic

compounds.

HAZARDOUS POLYMERIZATION: Will not occur.

#### **SECTION 6: HEALTH HAZARD DATA**

#### **HEALTH RISKS AND SYMPTOMS OF OVEREXPOSURE:**

**EYES:** Irritation, burning, tearing, and redness.

SKIN: Moderate irritation or defatting of skin upon prolonged or repeated contact.

**INGESTION:** Product is moderately toxic and may be harmful if swallowed; may produce central nervous system depression. Ingestion may result in abdominal pain, nausea, vomiting and diarrhea. If vomiting occurs spontaneously, do not allow vomitous to be breathed into the lungs as even a small quantity may result in aspiration pneumonitis.

**INHALATION:** Vapors irritate mucus membranes. Excessive exposure to vapors can cause headache, nausea, and vomiting.

#### **EMERGENCY AND FIRST AID PROCEDURES:**

EYES: Flush with cool water for at least 15 minutes. Call a physician.

**SKIN:** Remove contaminated clothing, wash skin with soap and water. Launder contaminated clohing before reuse. **INGESTION:** Give victim 2 glasses of water and induce vomiting. NEVER ADMINISTER ANYTHING BY MOUTH TO AN UNCONSIOUS PERSON. Get medical attention immediately.

**INHALATION:** Remove to fresh air. If not breathing give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No

#### SECTION 7: PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Dike spill area. Soak up with absorbent material and place in sealed metal containers for proper disposal.

WASTE DISPOSAL METHOD: Dispose of in accordance with local, state and federal EPA regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store in dry area. Keep away from open flames and high temperatures.

**OTHER PRECAUTIONS:** Minimize contact. Avoid breathing vapors. Practice good industrial hygiene and safe working practices.

## **SECTION 8: CONTROL MEASURES**

**RESPIRATORY PROTECTION:** Use NIOSH approved dust mask respirator under appropriate OSHA standards and regulations. A combination of both proper ventilation and respiratory protection would tend to eliminate most risks. **VENTILATION:** Local exhaust is recommended.

PROTECTIVE GLOVES: Recommended

EYE PROTECTION: Wear liquid chemical goggles. Contact lenses should not be worn.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Eye wash facility and safety shower recommended. Long sleeve shirts and pants

WORK/HYGIENIC PRACTICES: Wash hands with soap and water after using and before eating.

# **SECTION 9: REGULATORY INFORMATION**

D. O. T. PROPER SHIPPING NAME: Synthetic Resin Liquid

PROPER SHIPPING NAME: Synthetic Resin Liquid

HAZARD CLASS: NONE
UN/NA ID NUMBER: NONE
PACKING GROUP NONE

**SECTION 10: DISCLAIMER** 

Data and recommendations presented herein are based upon our and other researchers and are believed to be accurate. The products discussed are distributed without warranty (expressed or implied) and the customer shall make his own determination of suitability for his particular purpose.

# MATERIAL SAFETY DATA SHEET EPOXY.COM # 464 100% SOLIDS URETHANE COATING PART B

PRODUCT NAME: EPOXY.COM # 464100% URETHANE COATING PART B HMIS CODES: H F R P

PRODUCT CODE: 464B 3 3 1 --

#### SECTION 1: MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: EPOXY SYSTEMS, INC. ADDRESS: EPOXY SYSTEMS, INC. 20774 West Pennsylvania Ave

Dunnellon, FI 34431

 EMERGENCY NUMBER:
 1-800-633-8253 PERS
 DATE PRINTED:
 09/17/08

 INFORMATION NUMBER:
 1-352-489-1666
 NAME OF PREPARER:
 K. Fontaine

#### SECTION 2: HAZARDOUS INGREDIENTS/SARA III INFORMATION

HAZARDOUS COMPONENTSCAS NUMBEROSHA PELACGIH TLVWT %HDI Hompolymer28182-81-2NENE>99

Substances listed are present in concentration of 1% or greater, or 0.1% if cited as a potential Carcinogen in the OSHA hazards communication standard. Where proprietary ingredient is listed, the identity is available as provided in 29 CFR 1910 1200

NE - Not Established

## **SECTION 3: PHYSICAL/CHEMICAL CHARACTERISTICS**

SOLUBILITY IN WATER : Reacts

APPEARANCE AND ODOR : Clear to amber liquid, odorless

WEIGHT PER GALLON : 9.16 lbs (± 0.25)
EVAPORATION RATE : Slower than ether
PERCENT VOC BY VOLUME : Negligible

#### SECTION 4: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: >200° F METHOD USED: TCC

FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: Not determined UPPER: Not determined

**EXTINGUISHING MEDIA:** CO2, dry chemical, water not recommended **SPECIAL FIRE FIGHTING PROCEDURES:** Wear NIOSH/MSHA approved self contained breathing apparatus and full protective clothing. Use water to keep fire exposed containers cool. Water may be ineffective as extinguishing agent. **UNUSUAL FIRE AND EXPLOSION HAZARDS:** Pressure may build up in containers and creae explosion hazard.

#### **SECTION 5: REACTIVITY DATA**

STABILITY: Stable

CONDITIONS TO AVOID: Excessive heat.

INCOMPATIBILITY (MATERIALS TO AVOID): Oxidizing agents, strong acids & bases, Polymerization initiators,

alcohols, amines, water.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Carbon dioxide, nitrogen oxides, and organic compounds.

HAZARDOUS POLYMERIZATION: May occur.

- 1

## **SECTION 6: HEALTH HAZARD DATA**

#### HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

EYES: Irritation, burning, tearing, and redness.

**SKIN:** Moderate irritation or defatting of skin upon prolonged or repeated contact.

**INGESTION:** Abdominal pain, nausea, vomiting, and diarrea.

INHALATION: May be harmful if inhaled.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No

**EMERGENCY AND FIRST AID PROCEDURES:** 

EYES: Flush with cool water for at least 15 minutes. Call a physician.

SKIN: Remove contaminated clothing, wash skin with soap and water.

INGESTION: Do not induce vomiting. Get medical attention immediately.

INHALATION: Move to fresh air. Aid breathing if necessary. Call a physician.

## SECTION 7: PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Dike spill area. Absorb with inert absorbant material. Place in sealed containers for proper disposal.

WASTE DISPOSAL METHOD: Dispose of in accordance with local, state and federal EPA regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store in dry area. Keep away from open flames and high temperatures.

OTHER PRECAUTIONS: Minimize contact. Avoid breathing vapors. Practice good industrial hygiene and safe working practices.

#### **SECTION 8: CONTROL MEASURES**

**RESPIRATORY PROTECTION:** Use NIOSH approved dust mask respirator under appropriate OSHA standards and regulations. A combination of both proper ventilation and respiratory protection would tend to eliminate most risks.

**VENTILATION:** Local exhaust is recommended.

PROTECTIVE GLOVES: Recommended.

EYE PROTECTION: Wear liquid chemical goggles. Contact lenses should not be worn.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Eye wash facility and safety shower recommended. Long sleeve shirts and pants.

WORK/HYGIENIC PRACTICES: Wash hands with soap and water after using and before eating.

# **SECTION 9: REGULATORY INFORMATION**

D. O. T. PROPER SHIPPING NAME: Less Than 100# per container: Not Regulated by DOT

PROPER SHIPPING NAME: Environmentally hazardous substance, Liquid, N.O.S. (Hexamethylene Diisocyanate)

HAZARD CLASS: Class 9, Miscellaneous

UN/NA ID NUMBER: UN 3082
PACKING GROUP III

# **SECTION 10: DISCLAIMER**

Data and recommendations presented herein are based upon our and other researchers and are believed to be accurate. The products discussed are distributed without warranty (expressed or implied) and the customer shall make his own determination of suitability for his particular purpose.

2.