MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Epoxy.com #231 WATER EMULSION PRIMER PART A

HMIS CODES: H F R P

PRODUCT CODE: 231 A

SECTION 1: MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: Epoxy Systems, Inc.

ADDRESS: 20774 West Pennsylvania Ave

Dunnellon, Fl 34431

EMERGENCY NUMBER: 1-800-633-8253 **DATE PRINTED:** 11/13/09 **INFORMATION NUMBER:** 1-352-489-1666 **PREPARER:** K. Fontaine

SECTION 2: HAZARDOUS INGREDIENTS

ACGIH

HAZARDOUS COMPONENTS CAS NUMBER OSHA PEL TLV WT % CARCINOGEN

Epoxy Resin 25068-38-6 NE NE 20-25 NC

Methoxypropanol 107-98-2 100 ppm 100 ppm 1-5

Substances listed are present in concentration of 1% or greater, or 0.1% if cited as a potential Carcinogen in the OSHA hazards

communication standard. Where proprietary ingredient is listed, the identity is available as provided in 29 CFR 1910.1200.

NE - Not Established

SECTION 3: PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE 212° F

VAPOR DENSITY Not determined VAPOR PRESSURE Not determined

VOC

SOLUBILITY IN WATER Dispersable

APPEARANCE AND ODOR Low viscosity, milky liquid with a

mild odor

SPECIFIC GRAVITY (H20=1) 1.05

SECTION 4: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: >201 °F

METHOD USED:

FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: Not established UPPER: Not established

UPPER: NOT established

EXTINGUISHING MEDIA: Water fog, Dry Chemical, Foam, CO2

SPECIAL FIRE FIGHTING PROCEDURES: Full protective equipment including self contained breathing apparatus should be used. Water spray may be ineffective. If water is used, for nozzles are preferable. Water may be used to cool closed containers to prevent build up and possible auto ignition or explosion when exposed to extreme heat.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Closed containers may explode when exposed to extreme heat. Application to hot surfaces may require special precautions during emergency conditions overexposed to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention. Use National Fire Protection Association (NFPA) Class B extinguisher or extinguishing agent designed to extinguish flammable liquid fires.

SECTION 5: REACTIVITY DATA

STABILITY: Stable

CONDITIONS TO AVOID: Elevated temperatures

INCOMPATIBILITY (MATERIALS TO AVOID): Peroxides and Oxidizers
HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Thermal decomposition and

partial combustion may produce hazardous fumes which may contain the

following materials: Carbon Monoxides

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 6: HEALTH HAZARD DATA

HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Prolonged or repeated contact may cause skin and eye irritation.

HEALTH HAZARDS (ACUTE AND CHRONIC):

INHALATION: May cause irritation to upper respiratory tract.

SKIN: Prolonged contact may cause irritation.

EYE: Will cause injury that will persist for several days.

INGESTION: Can cause headaches and nausea.

CARCINOGENICITY:

NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED:

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Repeated exposure to this product may cause eye and respiratory tract irritation and respiratory sensitization.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Flush with water for at least 15 minutes. Get medical attention if irritation persists.

SKIN: Remove contaminated clothing. Wash exposed areas with soap and water.

INGESTION: Do not induce vomiting. Dilute with large amount of
 water. Seak medical attention.

INHALATION: In case of exposure to high vapor mist, remove person
 to fresh air. If breathing has stopped, administer artificial
 respiration and seek medical attention.

SECTION 7: PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Dike spill, absorb with inert material and collect for disposal. Prevent washing from entering waterways before being neutralized.

WASTE DISPOSAL METHOD: Observe local, state and Federal regulations for disposal.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store in a cool, dry, well ventilated area. Protect container against physical damage. Keep container away from incompatible material (see section 5).

OTHER PRECAUTIONS: Wash thoroughly after handling. Do not wear any contaminated clothing or shoes. Use good personal hygiene practices.

SECTION 8: CONTROL MEASURES

RESPIRATORY PROTECTION: Recommended if the product is misted.

VENTILATION: Local exhast.

PROTECTIVE GLOVES: Wear rubber gloves to prevent direct contact.

EYE PROTECTION: Wear splash-proof safety goggles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Eye wash & safety shower.
WORK/HYGIENIC PRACTICES: Wash thoroughly after handling. Do not wear

contaminated clothing or shoes. Use good personal hygiene

practices.

SECTION 9: REGULATORY INFORMATION

D. O. T. PROPER SHIPPING NAME: Water-Based Resin

PROPER SHIPPING NAME: Water-Based Resin
HAZARD CLASS: non-hazardous

UN/NA ID NUMBER:

SECTION 10: DISCLAIMER

Data and recommendations presented herein are based upon our and other researchers and are believed to be accurate. The products discussed are distributed without warranty (expressed or implied) and the customer shall make his own determination of suitability for his particular purpose.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: EPOXY.COM #231WATER EMULSION PRIMER PART B

HMIS CODES: H F R P

PRODUCT CODE: 231 B

SECTION 1: MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: EPOXY SYSTEMS, INC.

ADDRESS: 20774 West Pennsylvania Ave

Dunnellon, Fl 34431

EMERGENCY NUMBER: 800-633-8253 DATE PRINTED: 11/13/09
INFORMATION NUMBER: 352-489-1666 PREPARER: K. Fontaine

SECTION 2: HAZARDOUS INGREDIENTS

ACGIH

HAZARDOUS COMPONENTSCAS NUMBEROSHA PELTLVWT %CARCINOGENAliphatic Amine MixtureNENE30-40NOIsophoronediamine2855-13-2NENE1-5NO

Substances listed are present in concentration of 1% or greater, or 0.1% if cited as a potential Carcinogen in the OSHA hazards communication standard. Where proprietary ingredient is listed, the identity is available as provided in 29 CFR 1910.1200.

NE - Not Established

SECTION 3: PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE 212° F

VAPOR DENSITY Not determined VAPOR PRESSURE Not determined

VOC

SOLUBILITY IN WATER Dispersable

APPEARANCE AND ODOR Low viscosity, amber liquid with a

mild amine odor

SPECIFIC GRAVITY 1.05

(H20=1)

SECTION 4: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: NA

FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: 1.3%

UPPER: 6.0%

EXTINGUISHING MEDIA: Not Applicable

OSHA FLAMMABILITY CLASSIFICATION: Not Applicable

SPECIAL FIRE FIGHTING PROCEDURES: Full protective equipment including self contained breathing apparatus should be used. Water spray may be ineffective. If water is used, for nozzles are preferable. Water may be used to cool closed containers to prevent build up and possible auto ignition or explosion when exposed to extreme heat.

UNUSUAL FIRE AND EXPLOSION HAZARDS: During Emergency conditions
 overexposure to decomposition products may cause a health hazard.
 Symptoms may not be immediately apparent. Obtain medical attention.
 Closed containers may explode (due to the build up of steam
 pressure) when exposed to extreme heat.

SECTION 5: REACTIVITY DATA

STABILITY: This product is stable under normal storage conditions.

CONDITIONS TO AVOID: Elevated temperatures.

INCOMPATIBILITY (MATERIALS TO AVOID): Amines Peroxides and Oxidizers

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Thermal decomposition and partial combustion may produce hazardous fumes which may contain the following materials: Carbon Monoxides

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Prolonged or repeated contact may cause skin and eye irritation.

HEALTH HAZARDS (ACUTE AND CHRONIC):

INHALATION: May cause irritation to upper respiratory tract.

SKIN: Prolonged contact may cause irritation.

EYE: Will cause injury that will persist for several days.

INGESTION: Can cause headaches and nausea.

CARCINOGENICITY:

NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED:

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Repeated exposure to this product may cause eye and respiratory tract irritation and respiratory sensitization.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Flush with water for at least 15 minutes. Get medical attention if irritation persists.

 ${f SKIN:}$ Remove contaminated clothing. Wash exposed areas with soap and water.

INGESTION: Do not induce vomiting. Dilute with large amount of water. Seak medical attention.

INHALATION: In case of exposure to high vapor mist, remove person to fresh air. If breathing has stopped, administer artificial respiration and seek medical attention.

SECTION 7: PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Dike spill, absorb with inert material and collect for disposal. Prevent washing from entering waterways before being neutralized.

WASTE DISPOSAL METHOD: Observe local, state and Federal regulations for disposal.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store in a cool, dry, well ventilated area. Protect container against physical damage. Keep container away from incompatible material (see section 5).

OTHER PRECAUTIONS: Wash thoroughly after handling. Do not wear any contaminated clothing or shoes. Use good personal hygiene practices.

SECTION 8: CONTROL MEASURES

RESPIRATORY PROTECTION: Recommended if the product is misted.

VENTILATION: Local exhast.

PROTECTIVE GLOVES: Wear rubber gloves to prevent direct contact.

EYE PROTECTION: Wear splash-proof safety goggles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Eye wash & safety shower.

WORK/HYGIENIC PRACTICES: Wash thoroughly after handling. Do not wear contaminated clothing or shoes. Use good personal hygiene

practices.

SECTION 9: REGULATORY INFORMATION

D. O. T. PROPER SHIPPING NAME: Water-Based Resin

PROPER SHIPPING NAME: Water-Based Resin
HAZARD CLASS: non-hazardous

UN/NA ID NUMBER:

SECTION 10: DISCLAIMER

Data and recommendations presented herein are based upon our and other researchers and are believed to be accurate. The products discussed are distributed without warranty (expressed or implied) and the customer shall make his own determination of suitability for his particular purpose.