

- [Home](#)
- [Product Catalog](#)
- [About Us](#)
- [Adhesives](#)
- [Chemical Resistant](#)
- [Epoxy Coatings](#)
- [Flooring](#)
- [Installation](#)
- [Joints](#)
- [Mortars & Grouts](#)
- [Primers & Sealers](#)
- [Specifier's Info](#)
- [Structural](#)
- [Waterproofing](#)
- [MSDS & Tech Data](#)
- [Ordering Info](#)

The Right Product for the Right Job Since 1980



[\[Contact Us\]](#)

Acrylic Sealer

A Clear, non-yellowing protective coating

Epoxy.com Product #80

DESCRIPTION

ACRYLIC SEALER Product #80 (formerly known as **Epoxy.com Product #239**) is a clear acrylic solution formulated to create a clear, non-yellowing protective coating. **Product #80 ACRYLIC SEALER** provides a tough, UV and abrasion resistant film that effectively protects surfaces from moisture penetration, staining, dirt, dust, and wear. Providing a surface that is easy to clean and maintain, **Epoxy.com Product #80 ACRYLIC SEALER** is an excellent choice for both interior and exterior applications.

Epoxy.com Product #80 ACRYLIC SEALER is most commonly used as a sealer for **Epoxy.com Epoxy Terrazzo** and **Epoxy.com Polymeric Terrazzo** flooring systems. It is also used for sealing old and new concrete floors, Concrete Countertops, exterior ramps, decks, sidewalks, slate, and exposed aggregate surfaces.

ADVANTAGES

- UV resistant
- Excellent clarity and color retention
- Low maintenance finish
- Excellent abrasion and mar resistance

Seals substrate from moisture penetration

CONSIDERATIONS

- Do not apply below 50°F
- Contains solvent. Keep from ignition sources
- Must be applied with proper ventilation

APPLICATION

SURFACE PREPARATION

Prepare surface in accordance with **Epoxy.com, Technical Bulletins**. New concrete must be cured at least 30 days. All concrete curing compound must be mechanically removed, along with any foreign material. Old concrete must be structurally sound and prepped according to guidelines.

MIXING INSTRUCTIONS

Epoxy.com Product #80 ACRYLIC SEALER is a single component acrylic solution. Stir material in container prior to application. Do not reduce.

INSTALLATION

Apply by roller, brush, or applicator pad. Spread at an even rate between 300 and 500 square feet per gallon. Two coats are recommended for sealing applications.

CURE

Re-coat in 2 to 4 hours at 70⁰F with 50% RH. Low temperatures or high humidity may significantly increase cure time. Do not open to light traffic for at least 24 hours after application

CLEAN-UP

Clean tools with Xylene or lacquer thinner.

TECHNICAL DATA

Color	Clear
Mixing Ratio, by volume	Single Component
Solids Content, by volume	20%
VOC	746 g/L
Weight per Gallon, mixed	7.5-8.0 pounds

MAINTENANCE

After completing the application of **Epoxy.com Product #80 ACRYLIC SEALER**, the installer should provide the owner with maintenance instructions. If floors become slippery due to animal fats, oil, grease, or soap film, promptly remove contaminants and rinse thoroughly.

Epoxy.com Product #80 ACRYLIC SEALER is easily cleaned with neutral soaps or detergents. Routine mechanical scrubbing is recommended for all surfaces having a non-skid texture. Waxing is optional. Long periods of heavy traffic may cause wear patterns necessitating a maintenance application of a finish coat.

TECHNICAL SERVICE

Epoxy.com, Inc. provides services and consultations on material selection, specification, troubleshooting, and other information on the proper repair and protection of concrete surfaces. **Epoxy.com REPRESENTATIVES** are available to assist you at 352-533-2167

Proper mixing and installation is critical to the optimal success of all products. See [Installation Tips](#), [Techdata](#), & [MSDS](#) for more details on our products. Be sure to contact us with any questions and/or concerns that you have.

For more information please contact:

Epoxy.com

A Division of [Epoxy Systems, Inc](#)

A Vermont Corporation

USA

We have products that have passed the test of time as well as the best new [Systems](#) available today.

Since 1980 - 40 years of the highest quality products

Hours: 9AM-4PM Eastern Time (6AM-1PM Pacific Time)

Closed for lunch from 12Noon to 1PM

321-206-1833 Customer Service - Ordering and Order Status
Katey Lambert-Fontaine, VP - Chief Operations Officer
sales@epoxy.com

Technical Support
352-533-2167 Norm Lambert, President - Technical Support Director
info@epoxy.com

352-489-1666 Accounting and Administration
Debby Lambert, CEO, and CFO Debby Lambert, CEO, and CFO

352-489-1625 Fax line to all Departments

Copyright © 1994-2022 (**providing online information about the right product for the right job for over 25 years**) EPOXY.COM a division of Epoxy Systems, Inc. - Florida and Vermont. All rights reserved.



We accept MasterCard, Visa, American Express, Discover, or Wire Transfers.

[Home](#)

[Sales Terms](#)

[MSDS & Tech Data](#)

[Online Ordering Authorization Form](#)

[Add this page to Favorites](#)

[Secure Login](#)