
General Care and Maintenance Instructions of Epoxy Systems' Flooring Systems

I. GENERAL INFORMATION

EPOXYSYSTEMS' Flooring Systems demonstrate superior resistance to wear and abrasion. **EPOXYSYSTEMS'** Seamless Flooring Systems are designed to produce, long-term, seamless floor protection resistant to wear, chemical attack, and dirt penetration. **EPOXYSYSTEMS'** floors can be generally maintained with a routine program similar to any good-housekeeping procedures. Thorough sweeping and mopping to remove loose particles and soil along with prompt removal of grease and other contaminants will prevent most **EPOXYSYSTEMS'** Flooring Systems from early deterioration.

II. DAILY MAINTENANCE

- A. **DAILY SWEEP - EPOXYSYSTEMS' SEAMLESS FLOORS.** Routine sweeping, and mopping prevents damage to the finish from the grinding effect of minute abrasive particles common to work areas.
- B. Mopping should only be done with a clean polyester mop and clear clean water with appropriate detergents and/or degreasers added at recommended dosing. Don't forget to use a healthy dose of "elbow grease".
- C. Promptly remove grease and other contaminants.
- D. Promptly **RINSE OFF** all chemical solutions that may attack the surface. Floors should be rinsed thoroughly with lots of clear, clean water.

III. WEEKLY MAINTENANCE

- A. **ALL EPOXYSYSTEMS' FLOORS** should be mopped on a regular basis with a neutral detergent or soap, and thoroughly rinsed. Water should be changed frequently and mops rinsed often. See mopping in **DAILY MAINTANANCE** above
- B. Severe spillage or routine major contamination also requires special cleaning protocols. The following procedures for **PROBLEM AREAS** may also be applied in these instances.
- C. **FLOORS** may require the use of a mechanical scrubber or a firm bristle brush to reach the base of the texture.

IV. PROBLEM AREAS

Severe problem areas may be treated as follows:

- A. **GREASE:** Greasy deposits are best attacked with Trisodium phosphate or a commonly available bio-degradable solvent. Contact your **Janitorial Supply Specialist** for specifics.
- B. **DAIRY PRODUCTS** should be removed immediately as they may cause staining to some surfaces.
- C. **TIRE MARKS:** Scrub thoroughly with a stiff bristle brush using the same bio-degradable solvent as mentioned above.
- D. When attacking **STUBBORN DIRT OR STAINS**, allow the cleanser to work for you by allowing it to stand an extra moment or so on the problem area before thoroughly rinsing with clean water.

E. It is imperative that strong chemicals be rinsed from the surface of any floor as soon as possible.

V. WAXING AND POLISHING

EPOXYSYSTEMS' FLOORS need not be waxed or polished. However, should wear areas appear in heavy traffic areas, waxing or polishing with a standard commercial product may enhance the finish.

Failure to follow this procedure will result in excessive deposits of dirt in the anti-skid areas, and may cause long term damage to your flooring system.

For more information about this product or any other Epoxy Systems™ product, please contact:

Epoxy Systems, Inc.

Florida and Vermont

(352) 489-1666

(352-465-3497(fax)

info@epoxy.com (email)

www.epoxy.com (WWW)

This information is presented in good faith to assist in determining whether this product is suitable for application. No warranty or representation, however, is intended or made, nor is protection from any law or patent to be inferred, and all patent rights reserved.